

HST KÄYRÄT 45°



KÄYRÄ 45°
EN 10253-3/4

4404

DN	OD	T	R	D
15	21,3	X 2,0	31,8	3D
20	26,9	X 2,0	28,5	3D
25	33,7	X 2,0	38	3D
32	42,4	X 2,0	47,6	3D
40	48,3	X 2,0	57,1	3D
50	60,3	X 2,0	76,2	3D
50		X 3,0	76,2	3D
65	76,1	X 2,0	96	3D
65		X 3,0	96	3D
80	84	X 2,0	120	3D
80	88,9	X 2,0	114,3	3D
80		X 3,0	114,3	3D
100	104	X 2,0	150	3D
100	114,3	X 2,0	152,5	3D
100		X 3,0	152,5	3D
125	129	X 2,0	187,5	3D
125	139,7	X 2,0	190,5	3D
125		X 3,0	190,5	3D

KAROTEK

HST KÄYRÄT 45°



KÄYRÄ 45°
EN 10253-3/4

4404

DN	OD	T	R	D
150	154	X 2,0	225	3D
150	168,3	X 2,0	228,5	3D
150		X 3,0	228,5	3D
200	204	X 2,0	300	3D
200	206	X 3,0	300	3D
200	219,1	X 2,0	305	3D
200		X 3,0	305	3D
250	254	X 2,0	375	3D
250	256	X 3,0	375	3D
250	273	X 3,0	381	3D
300	306	X 3,0	450	3D
300	323,9	X 3,0	457	3D
350	355,6/356	X 3,0	533	3D
400	406/406,4	X 3,0	610	3D

KAROTEK

Muut mitat ja laadut kysymällä erikseen.